

PALLET & CARGO  
X-RAY IMAGING SYSTEM

# XRC 150-165DV (200kV)



**XRC 150-165DV** x-ray baggage scanner facilitates the operators use thanks to the various image processing functions, hazard alarm, advanced computer technology and the best in class software with its **200kV** generator source. It makes it extraordinarily easy to detect threats such as cutting tools, explosive narcotics and reduces the rate of error. It provides unique image quality by showing the scanned organic, inorganic and mixed items in different colors thanks to its multi-diode structure and quality in imaging of scanned objects.

It is manufactured with **dual view (DV)** technology. Thanks to its 2 generator sources, it provides high resolution and detailed imaging in horizontal and vertical angles. The visuals can be accessed with a single scan without the need to re-place the packages in a different orientation. Thus, hidden objects in the luggage are detected more easily and quickly.

It is designed with the latest technology to scan medium and large packages on a pallet. XRC 150-165DV is one of the most suitable solutions for use in high security facilities such as freight companies, terminals, airports, customs and general cargo.

# TECHNICAL DATA XRC 150-165DV (200kV)

## PHYSICAL PROPERTIES

Tunnel Size	: 1540 mm x 1660 mm
(W x H)	: 60,63 in x 65,35 in
Dimensions	: 8180 mm x 2505 mm x 2865 mm
(L x W x H)	: 322,05 in x 98,62 in x 112,80 in
Approx. Weight Unpacked	: ~6100 kg (13448 lbs.)
Conveyor Height	: 385 mm (15,16 in)
Conveyor Load Capacity	: 3000 kg (6614 lbs.) Evenly Distributed
System Power	: 120/220V AC $\pm$ 10% 50/60 Hz, 15A/8A
Conveyor Speed	: 0,20 m/sec. Forward or Reverse

## X-RAY GENERATOR & IMAGE PERFORMANCE

Steel Penetration <sup>1</sup>	: 50 mm guaranteed; 52 mm typical
Wire Resolution <sup>1</sup>	: 36 AWG guaranteed; 38 AWG typical
Anode Voltage	: 200kV, operating at 200kV
Tube Current	: 1,2 mA
Beam Direction	: 1st Generator - Vertically downward 2nd Generator - Horizontally sideward
Article Separation	: Low Z, Medium Z, High Z to 0,5 Z Accuracy Organic, InOrganic, Metallic
Cooling	: Oil and forced air cooling

## COMPUTER SPECIFICATIONS

Processor	: Intel® Core™ i5 (or superior)
Monitor	: Dual 21,5" Flat LCD (or superior)
Memory	: 4 GB RAM (or superior)
Video Card	: 2 GB (or superior)
Hard Drive	: 1 TB (or superior)
USB Port	: 6 port (or superior)
Operating System	: Linux

## OPERATING ENVIRONMENT

Storage / Operating Temperature	: -20°C to 50°C / 0°C to 40°C (-4°F to 122°F / 32°F to 104°F)
Relative Humidity	: 0% to 95% non-condensing
Duty Cycle 100% (24 Hours), No warm-up required	

## HEALTH AND SAFETY

All X-Ray Center Ltd products meet all applicable international health and safety regulations.  
 US FDA Federal Standard 21CFR 1020.40  
 Health and Safety at Work Act 1974-compliant 6 : Available  
 Film Safety : ISO 1600 / 33 DIN  
 CE Compliance : Certified  
 FCC & IEC Compatibility : Available  
 IP 20 Safety : Certified  
 Maximum level of radiation the exterior panels come in contact with is 0.1 mR/hour

## OPTIONAL FEATURES

Barcode Reader System  
 External Camera Archiving  
 Remote Viewing Station  
 Recheck Station  
 Network Supervisory System (NSS)  
 Remote Access Connection  
 Smart Card Login

## OPTIONAL ACCESSORIES


External UPS (For system)  
 Operator Console (Open-Closed/Adjustable/I-stand)  
 21,5" - 27" Flat Monitor  
 Input / Output Rollers  
 Test Kit (STP/ASTM)  
 Protective Cover  
 Search Table  
 Tray Return System (Motorized/Gravity)  
 Inclined Conveyor  
 Ultrasonic Rat Repellent  
 Radiation Meter

## STANDARD IMAGE PROCESSING FEATURES

Perfect View (Detail Enhancement) (PV)  
 Edge Enhancement (EE)  
 Pseudo Color (PS)  
 Organic Materials (OM)  
 Inorganic Materials (IM)  
 Black & White (B/W)  
 Inverse Colors (IN)  
 High Penetration (HP)  
 Variable Edge Enhancement (+E -E)  
 Variable Density (+D -D)  
 Variable Gamma (+G -G)  
 Variable Color Separation (+C -C)  
 Zoom (64x)  
 Sniper Zoom  
 Recall Previous Images  
 Manual/Automatic Archive  
 Annotated Archive  
 Multi Energy Viewer (4 - 6 Color)  
 Atomic Number Display (Z Value)

## STANDARD FEATURES

Programmable Function Keys  
 Parcel Counter  
 Date and Time Display  
 Virtual Threat Image Projection (TIP)  
 Organic/Inorganic Threat Alarm  
 Operator Training Program (OTP)  
 UPS (For Computer Supply)  
 Multi Languages  
 Self Diagnosis  
 Generator Timer  
 Automatic Stop Conveyor  
 Bi-Directional Scanning  
 Emergency Stop Buttons



<sup>1</sup>As tested on X-Ray Center Ltd. test piece. Conveyor speed is 0.20 m/sec.

Due to continuous product development, X-Ray Center reserves the right to change specifications without notice.

